



On-Premises Hardmount Washer-Extractors


SC020, SC030, SC040, SC060, SC080, SC100

Features

- Rigid mounted, normal spin, 100G factor
- Stainless steel top and front panel
- Stainless steel drum and tub
- High capacity water inlets
- Large drain valve
- Large door opening for easy loading & unloading
- Industry-leading flexible water level settings
- Patented Fill and Drain leak detection saves water
- Lighter, computer-optimized frame
- Designed to reduce sound and vibration levels
- Quantum™ Gold Control
 - easy to operate, easy to program
 - flexibility of 30 programmable cycles
- Quantum™ Standard Control
 - four cycle selections
 - two water levels and manual programming

Options


- 200G factor (SC020-SC080 with Quantum™ Gold)
- 165G factor (SC0100 with Quantum™ Gold)
- Stainless steel side panels
- Chrome door
- Steam heating version
- Electrical heating version



ROBUST
DESIGN




LARGE
DRAIN VALVE



LARGE DOOR
OPENING



LOW WATER
CONSUMPTION



Model	SC020	SC030	SC040	SC060	SC080	SC100	
Control Option	Gold/Standard	Gold/Standard	Gold/Standard	Gold/Standard	Gold/Standard	Gold/Standard	
Capacity – [kg (lb)]	9.1 (20)	13.1 (30)	18.1 (40)	27.2 (60)	36.3 (80)	45.4 (100)	
Overall Width – [mm (in)]	660 (26)	737 (29)	778 (30.6)	865 (34.1)	1054 (41.5)	1054 (41.5)	
Overall Depth – [mm (in)]	784 (30.9)	896 (35.3)	1073 (42.3)	1135 (44.7)	1196 (47.1)	1298 (51.1)	
Overall Height – [mm (in)]	1092 (43)	1143 (45)	1199 (47.2)	1267 (49.9)	1453 (57.2)	1453 (57.2)	
Cylinder Diameter – [mm (in)]	533 (21)	610 (24)	668 (26.3)	762 (30)	914 (36)	914 (36)	
Cylinder Depth – [mm (in)]	350 (13.8)	406 (16)	515 (20.3)	559 (22)	556 (21.9)	657 (25.9)	
Cylinder Volume – [l (cu. ft.)]	79.3 (2.8)	119 (4.2)	178 (6.3)	255 (9.0)	365 (12.9)	430 (15.2)	
Door Opening Size – [mm (in)]	295 (11.6)	363 (14.3)	414 (16.3)	414 (16.3)	470 (18.5)	470 (18.5)	
Door Bottom to Floor – [mm (in)]	365 (14.4)	356 (14)	370 (14.6)	379 (14.9)	455 (17.9)	455 (17.9)	
Water Inlet Connection – [mm (in)]	2 @ 19 (0.75)	2 @ 19 (0.75)	2 @ 19 (0.75)	4 @ 19 (0.75)	4 @ 19 (0.75)	4 @ 19 (0.75)	
Drain Diameter – [mm (in)]	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)	
Drain Height to Floor – [mm (in)]	99 (3.9)	109 (4.3)	114 (4.5)	124 (4.9)	130 (5.1)	130 (5.1)	
Total # of Speeds	6,9	6,9	6,9	6,9	6,9	6,9	
Cylinder Speeds – [RPM (G-Force)]	Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)	28 (0.4)
	Wash	51 (0.8)	48 (0.8)	46 (0.8)	43 (0.8)	39 (0.8)	39 (0.8)
	Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)	70 (2.5)
	Very Low	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)	230 (27)
	Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)	396 (80)
	Medium	579 (100)	542 (100)	518 (100)	485 (100)	443 (100)	443 (100)
	High	648 (125)	606 (125)	579 (125)	542 (125)	495 (120)	495 (120)
	Very High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)	542 (150)
Ultra High	819 (200)	766 (200)	733 (200)	686 (200)	626 (200)	568 (165)	
Voltage wires/ Circuit Breaker – FLA	120/60/1	15.IX	15.XII	20-15	N/A	N/A	N/A
	200-208/220-240/50/60/3/1/3	15-4 (1 Ph) 15-3 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-11 (1 Ph) 15-7 (3 Ph)	20-15 (1 Ph) 15-9 (3 Ph)	20-16 (1 Ph) 15-10 (3 Ph)
	200-208/220-240/50/60/3/3	30-22	30-22	50-41	50-41	80-73	80-74
	440-480/50/60/3/3	15-2	15-3	15-3	15-4	15-6	15-6
Shipping Dimensions Approx. – [mm (in)]	Width	711 (28)	800 (31.5)	826 (32.5)	953 (37.5)	1118 (44)	1118 (44)
	Depth	859 (33.8)	973 (38.3)	1105 (43.5)	1191 (46.9)	1384 (54.5)	1486 (58.5)
	Height	1255 (49.4)	1303 (51.3)	1361 (53.6)	1430 (56.3)	1514 (59.6)	1514 (59.5)
Motor Power Consumption – [kW (HP)]	0.75 (1)	0.75 (1)	1.5 (2)	2.2 (3)	3.7 (5)	3.7 (5)	
Net Weight – [kg (lb)]	154 (340)	200 (440)	245 (540)	308 (680)	567 (1250)	581 (1280)	
Shipping Weight – [kg (lb)]	172 (380)	218 (480)	263 (580)	327 (720)	590 (1300)	603 (1330)	
Slat Crate Shipping Weight – [kg (lb)]	209 (460)	263 (580)	308 (680)	381 (840)	649 (1430)	662 (1460)	
Agency Approvals	cETLus, CE	cETLus, CE	cETLus, CE	cETLus, CE	cETLus, CE	cETLus	

